









JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 04331412 A (43) Date of publication of application: 19.11.1992

H02H 3/087 (51) Int. CI HOZH 3/20, H02H 7/20, H02J 1/00

(71) Applicant: MITSUBISHI ELECTRIC CORP

HAYASHI SHIGEO

IMAI MAKOTO

(72) Inventor:

03101081 (21) Application number:

07.05.1991 22) Date of filing: (54) CIRCUIT PROTECTED FROM OVERCURRENT

stops flowing. Therefore, the transistor 2 is cut off between the collector and the emitter. By this method, a power circuit can be protected from both an overcurtransistor 2 is branched and becomes small and finally rent and a reverse voltage.

COPYRIGHT: (C)1992, JPO&Japio

transistor with a second transistor connected to the

first transistor.

PURPOSE: To pratect 4 power circuit from both an overcurrent and a reverse voltage by controlling a first

(57) Abstract:


nected to a transistor 2. When a short occurs in a load circuit due to the breakage or other troubles of a cable

CONSTITUTION: A PNP-type transistor 4 is con-

or and an emitter of the transistor 2. Thereupon, the

potential of a cathode of a diode 3 drops and a poten-

and then a current running in the load circuit increases, a potential difference is generated between a connec-



BEST AVAILABLE COPY

21/03/2005







